



Model	HTC-8116F-NVR
Video & audio input	
Network video input	16CH
Video & audio output	
HDMI output	800x600, 1024x768, 1280x1024, 1440x900, 720P, 1080P
VGA output	800x600, 1024x768, 1280x1024, 1440x900, 720P, 1080P
Audio output	1PCS RCA Port(line level , impedance : 1kΩ)
Video & audio code and decode parameters	
Record resolution	D1/HD1/CIF/720P/960P/1080P
Playback resolution	720P 30/420FPS 1080P 100/120FPS
Motion detection	Motion Detection Depend on NVR
Synchronously playback channels	1/4/9/16CH
Record management	
Record & Snapshot mode	manual recording, regular recording, motion recording, alarm recording, events recording
Playback mode	regular playback,alarm playback,motion detection playback,events playback
Backup mode	regular backup, events backup, manual backup
Hard driver	
Mode	2*SATA
HDD capacity	each port support max 4TB HDD
External port	
Voice intercom	1PCS RCA Port(Level : 2.0Vp-p, impedance : 1kΩ)
Internet port	1PCS RJ45 10M / 100M/1000M adaptive Ethernet port
USB port	1*USB2.0 1*USB3.0
Alarm input	NO
Alarm output	NO
Network Management	
Network protocol	NTP、SMTP、PPPoE、DDNS、FTP、ARSP、WIFI、3G
Other	
Power supply	DC12V
Power consumption(without HDD)	≤18W
Work temperature	-10℃-- + 55℃
Work humidity	10%--90%
Case	1U
Size(W*L*H(cm))	335*255*50mm
Net weight(without HDD)	1.36kg
Gross weight(without HDD)	2.23kg
Color box size(L*W*H(cm))	39*30*11cm
Packing(pcs/carton)	5
Carton size (L*W*H(cm))	57*40.7*32.6cm
Gross weight(kg)	12.04kg